



4105 - SPECIFICATION FOR RECLAIMING ASPHALT CONCRETE

4105 - 1 DESCRIPTION

- 1.01 The work shall consist of reclaiming asphalt concrete and placing in stockpile(s).

4105 - 2 MATERIALS

4105 - 3 CONSTRUCTION

- 3.01 The asphalt concrete shall be removed with a self loading cold milling machine equipped with automatic controls for grade and slope.
- 3.02 The width and depth of the asphalt concrete to be reclaimed shall be as indicated on the paving plans.
The roadway adjacent to the reclaimed trench may be reclaimed to remove any surface irregularities and to obtain a uniform cross slope prior to the application of the final lift of asphalt concrete.
- 3.03 Before reclaiming, the asphalt concrete shall be cleaned of all debris.
- 3.04 After reclaiming the asphalt concrete, any loose material shall be removed.
- 3.05 Water accumulations in the reclaimed trench shall be immediately removed. Failures caused by water or any other contaminant shall be immediately repaired.

Stockpile Construction

- 3.06 The reclaimed material shall be stockpiled in accordance with Specification 3600 For Stockpiling Aggregates.
- 3.07 A bed of aggregate, as approved by the Engineer, shall be maintained under the stockpile to prevent contaminating the reclaimed material with deleterious material.

4105 - 4 MEASUREMENT

- 4.01 Reclaimed asphalt concrete shall be measured in tonnes.
- 4.02 Reclaimed asphalt concrete that is wasted, unusable or contaminated shall be measured and deducted from the contract quantities.

4105 - 5 PAYMENT

- 5.01 Payment for Reclaimed Asphalt Concrete shall be at the contract unit price per tonne. The unit price shall be full compensation for completing the work except for those activities for which specific provisions for payment is made in this section.
- 5.02 If the contract includes a bid item for Hauling Reclaimed Asphalt Concrete; payment shall be made in accordance with Specification 2405 For Hauling On The Basis Of The Kilometre.